

DC DIAPHRAGM PUMP



DP-60

FEATURE

- * Portable and simple installation
- * Self suction capability
- * Built-in pressure switch and overflow drain valve
- * Corrosive-resistant
- * Low noise
- * High pressure
- * Medium temperature up to 60°C

APPLICATION

- * Mist cooling system
- * Water pressure booster
- * Vehicle cleaning
- * Reverse osmosis water purification system (RO)
- * Water filter
- * Water treatment
- * Chemistry metering
- * Printing industry
- * Sanitary industry
- * Environmental protect
- * Sea water desalination (on ship)



DP-125

Model	Voltage (V)	Max. Current (A)	Max. Capacity		Speed (rpm)	Max. Pressure		Suction (m)	Pressure Switch		Power (w)
			(usg/min)	(L/min)		(psi)	(Mpa)		(psi)	(Mpa)	
DP-60	12	7	1.4	5.3	1200	60	0.42	5	60	0.42	40
DP-125	24	1	0.26	1	375	125	0.86	5	125	0.86	10



THONG FATT JAYA MACHINERY HARDWARE SDN. BHD.

同發機械五金有限公司 (176024-V)

707-709, Jalan Kuala Kangsar, Taman Tasek Jaya,
31400 Ipoh, Perak, Malaysia.
Tel: 00-605-5468 659, 5455 751, 5479 196, 5454 107
Fax: 00-605-5482 282, 5474 753
Email: tfjaya@streamyx.com / tfjaya@tm.net.my
Website: <http://www.thongfattjaya.com.my>

