



# POWER SPRAYER

## TENMAR PETROL ENGINE SET

**FT-40A + GX 200**



**FT-40A + TENMAR GX 200**

### SPECIFICATION DATA

POWER SPRAYER		
Sprayer	Model	TENMAR FT-40A
	Type	Tri-cylinder Plunger Pump
	Piston No. x Diameter x Stroke	3 x 30mm x 20mm
	Speed	800~1000 rpm
	Suction	35~41.5 L/min
	Pressure	20~45 kgf/cm <sup>2</sup>
Irrigation	Speed	800~1000 rpm
	Suction	35~41.5 L/min
	Pressure	10 kgf/cm <sup>2</sup>
Net Weight		13.5 kg
PETROL ENGINE		
Engine	Model	TENMAR GX200
	Engine Type	Air-cooled, 4-Stroke, OHV 25° Inclined Cylinder, Horizontal Shaft
	Displacement	196 ml
	Bore X Stroke	68 X 54 mm
	Compression Ratio	8.5:1
	Max. Output Power	6.5 hp / 3600 rpm
	Max. Torque	1.35 kg.m / 2500 rpm
	Fuel Consumption	230 g/hp-hr
	Ignition System	Transistorised Pointless Ignition (TCL)
	Fuel Tank Capacity	3.6 L
	Lube Oil Capacity	0.6 L
	Net Weight	16 kg
	Dimension (LXWXH)	425 X 380 X 390 mm



**THONG FATT JAYA MACHINERY HARDWARE SDN. BHD.**

**同發機械五金有限公司** (176024-V)

707-709, Jalan Kuala Kangsar, Taman Tasek Jaya,  
31400 Ipoh, Perak. Malaysia.  
Tel: 00-605-5468 659, 5455 751, 5479 196, 5454 107  
Fax: 00-605-5482 282, 5474 753  
Email: tfjaya@streamyx.com / tfjaya@tm.net.my  
Website: <http://www.thongfattjaya.com.my>