

Frame Size	Poles	Installation Dimensions (mm)																						
		Foot Mounted								Flange Mounted								Shaft				General		
		A	A/2	B	C	H	K	AB	HD	M	N	P	S	T	HF	R	Flange No. / Holes	D	E	F	G	AC	AD	L
63	2,4	100	50	80	40	63	7	135	180	115	95	140	10	3	130		FF115 / 4	11	23	4	8.5	130	70	225
71	2,4,6	112	56	90	45	71	7	150	195	130	110	160	10	3.5	145		FF130 / 4	14	30	5	11	145	80	250
80	2,4,6,8	125	62.5	100	50	80	10	165	214	165	130	200	12	3.5	185		FF165 / 4	19	40	6	15.5	175	145	295
90S	2,4,6,8	140	70	100	56	90	10	180	250	165	130	200	12	3.5	195		FF165 / 4	24	50	8	20	195	155	315
90L				125																				340
100L	2,4,6,8	160	80	140	63	100	12	205	270	215	180	250	15	4	245		FF215 / 4	28	60	8	24	215	180	385
112M	2,4,6,8	190	95	140	70	112	12	230	300	215	180	250	15	4	265		FF215 / 4	28	60	8	24	240	190	400
132S	2,4,6,8	216	108	140	89	132	12	270	345	265	230	300	15	4	315		FF265 / 4	38	80	10	33	275	210	470
132M				178																				510
160M	2,4,6,8	254	127	210	108	160	15	320	420	300	250	350	19	5	385		FF300 / 4	42	110	12	37	330	255	615
160L				254																				670
180M	2,4,6,8	279	140	241	121	180	15	335	455	300	250	350	19	5	430		FF300 / 4	48	110	14	42.5	380	280	700
180L				279																				740
200L	2,4,6,8	318	159	305	133	200	19	395	545	350	300	400	19	5	480		FF350 / 4	55	110	16	49	420	305	770
225S	4,8	356	178	286	149	225	19	435	555	400	350	450	19	5	535		FF400 / 8	60	140	18	53	470	335	815
225M	2			55														110	16	49	820			
	4,6,8			60														140	18	53	845			
250M	2	406	203	349	168	250	24	490	615	500	450	550	19	5	595		FF500 / 8	60	140	18	53	510	370	910
	4,6,8																	65			58			
280S	2	457	229	368	190	280	24	550	680	500	450	550	19	5	650		FF500 / 8	65	140	18	58	580	410	985
	4,6,8																	75		20	67.5			
280M	2	457	229	419	190	280	24	550	680	500	450	550	19	5	650		FF500 / 8	65	140	18	58	580	410	1035
	4,6,8																	75		20	67.5			
315S	2	508	254	406	216	315	28	635	845	600	550	660	24	6	---		FF600 / 8	65	140	18	58	645	530	1160
	4,6,8,10																	80	170	22	71			1270
315M	2	508	254	457	216	315	28	635	845	600	550	660	24	6	---		FF600 / 8	6	140	18	58	645	530	1190
	4,6,8,10																	80	170	22	71			1300
315L	2	508	254	508	216	315	28	635	845	600	550	660	24	6	---		FF600 / 8	65	140	18	58	645	530	1190
	4,8																	80	170	22	71			1300
355M	2	610	305	560	254	355	28	730	1010	740	680	800	24	6	---		FF740 / 8	75	140	20	67.5	710	655	1500
	4,6,8,10																	95	170	25	86			1530
355L	2	610	305	630	254	355	28	730	1010	740	680	800	24	6	---		FF740 / 8	75	140	20	67.5	710	655	1500
	4,6,8,10																	95	170	25	86			1530